

**FOOD CONTACT COMPLIANCE DECLARATION**  
**No 24-12**

1. Business Operator Address	UAB Lietpak Čekoniškės, Vilnius District LT-14207 Lithuania																			
2. Product Group (Type of Packaging) Trade Names/Art. Nos. of Packaging) Composition	VAKPAK SV, SSV  PA/PE clear or colored																			
3. References to regulations which are complied with.	<p>We state that the above referenced material complies with:</p> <ol style="list-style-type: none"> <li>1. Regulation (EC) No. 1935/2004 of the European Parliament and of the Council of 27<sup>th</sup> October 2004 on materials and articles to come into contact with food (and amendments to date)</li> <li>2. Commission Regulation (EC) No. 2023/2006 22<sup>nd</sup> December 2006 on good manufacturing practice for materials and articles intended to come into contact with food. (and amendments to date)</li> <li>3. Commission Regulation EC 10/2011 and changed by Ordinance (UE) 1282/2011EC; 1183/2012EC; 202/2014EC; 2015/174EC; 2016/1416EC; 2017/752EC; 2018/79EC; 2018/831EC; 2018/213EC; 2019/37EC; 2019/1338EC; 2020/1245EC; 2023/1442EC and 2023/1627EC All these directives establish the list of monomers and other starting substances, as well as additives, admitted for the manufacture of plastics.</li> <li>4. Directive 94/62/EC and its amendments 2004/12/CE relating to packaging and packaging waste which establish a limit to the total content of heavy metals *(lead, cadmium, mercury and chromium-VI) in the final polymer.</li> <li>5. Commission Regulation (EC) 1895/2005 of 18 November 2005 on the restriction of use of certain epoxy derivatives in materials and articles intended to come into contact with food.</li> </ol>																			
4. Substance/s used with restriction/s (i.e. Monomers, starting substances & Additives)	<p>Substances subject to group specific migration limits:</p> <table border="1" data-bbox="528 1579 1439 1937"> <thead> <tr> <th>Substances</th> <th>SML, mg/kg</th> <th>CAS</th> </tr> </thead> <tbody> <tr> <td>Octadecyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl) propionate</td> <td align="center">6</td> <td align="center">0002082-79-3</td> </tr> <tr> <td>Zinc</td> <td align="center">5</td> <td align="center">-</td> </tr> <tr> <td>1-Hexene</td> <td align="center">3</td> <td align="center">0000592-41-6</td> </tr> <tr> <td>Caprolactam</td> <td align="center">15</td> <td align="center">000105-60-2</td> </tr> <tr> <td>Hexamethylenediamine</td> <td align="center">2.4</td> <td align="center">000124-09-04</td> </tr> </tbody> </table>		Substances	SML, mg/kg	CAS	Octadecyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl) propionate	6	0002082-79-3	Zinc	5	-	1-Hexene	3	0000592-41-6	Caprolactam	15	000105-60-2	Hexamethylenediamine	2.4	000124-09-04
Substances	SML, mg/kg	CAS																		
Octadecyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl) propionate	6	0002082-79-3																		
Zinc	5	-																		
1-Hexene	3	0000592-41-6																		
Caprolactam	15	000105-60-2																		
Hexamethylenediamine	2.4	000124-09-04																		

	Maleic anhydride	30	000108-31-6						
	vinylidene fluoride	5	75-38-7						
	Boric acid	6	10043-35-3						
	Aluminium	1	-						
	Acetic acid, vinyl ester	12	108-05-4						
	2,6-ditertbutyl-p-cresol	3	128-37-0						
	Hexafluoropropylene	0.01	116-15-4						
	Isophthalic acid	5	0000121-91-5						
	Copper	5	-						
	phosphorous acid, tris(2,4-di-tert-butylphenyl)ester	60	31570-04-4						
	terephthalic acid	7.5	100-21-0						
	3,5-di-tert-butyl-4-hydroxybenzylphosphonic acid, monoethyl ester, calcium salt	6	65140-91-2						
	1,1,1-trimethylolpropane	6	77-99-6						
	Titanium dioxide	60	13463-67-7						
	Tris(nonylphenyl)phosphite	30	-						
5. Substance/s used which are subject to restrictions in food ('dual use additives')	E170; E172; E180; E296; E355; E432; E470a,b; E530b; E551; E553b; E570; E900; E1521.								
6. Specification on the end use of the material	<p>1. The Product has been tested according to Directive 10/2011 EEC according the basic rules necessary for testing migration of the constituents of plastic materials and articles intended to come into contact with foodstuffs and according the list of simulants to be used for testing migration of constituents of plastic materials and articles intended to come into contact with foodstuffs.</p> <p>The simulants used for testing migration are:</p> <table> <tbody> <tr> <td>10% Ethanol</td> <td>simulant A</td> </tr> <tr> <td>3% acetic acid</td> <td>simulant B</td> </tr> <tr> <td>Olive Oil</td> <td>simulant D2</td> </tr> </tbody> </table> <p>2. Lietpak performs tests on its mentioned products based on all the simulants listed above. (and the product meets the global migration limit as laid down in the regulations)</p> <p>Test conditions: into 3% acetic acid 8h. 100°C and 10 days at 60°C; into olive oil 8h. 121°C and 10 days at 60°C; into 10% ethanol 8h. 100°C and 10 days at 60°C.</p>			10% Ethanol	simulant A	3% acetic acid	simulant B	Olive Oil	simulant D2
10% Ethanol	simulant A								
3% acetic acid	simulant B								
Olive Oil	simulant D2								

	Determination of metals in 3% acetic acid.
7. Condition of use	<p>The film could withstand thermal treatment of 121°C for 2 hours.</p> <p>Material in principle could be frozen. During freezing and while frozen, material will gradually be losing its flexibility as the temperature will go down. Customer should check if remaining properties are enough at given use conditions.</p>
8. Type or types of food with which it is intended to be put in contact	aqueous, acidic, fatty
9. ratio of food contact surface area to volume used	6 dm <sup>2</sup> /kg
10. Compliance with articles on functional barriers	Is not used
11. Declaration of use of recycle from an authorised process	The material does not contain any recycles
12. Declaration that the recycling process has been authorised	Not Applicable - See above section 11
13. Declaration that the input plastic, process and recycle meet the authorisation specification	Not Applicable - See above section 11
14. Declaration of quality assurance system meets the requirements of section B of annex II of 2023/2006	We confirm that our quality assurance system meets the requirements of section B of annex II of 2023/2006
15.	This Declaration only applies if the film supplied by UAB Lietpak is used properly. The company manufacturing and packaging the product is responsible for checking the whether the packaging is suitable for proposed application.
16. Storage	Products must be stored in premises with a roof which is protecting the product against direct sunlight, under 15-25°C temperature, 40-60 % relative humidity and at least 1m distance from heating appliances.
17. Date 2 of May 2024 Valid till 31.05.2025	UAB Lietpak Quality Assurance Z.D.