

PRODUCT INFORMATION

Customer:	-	Art.no:	16620
Name of product:	TRIO 200	Packed in:	-
Field of application:	WRAPPING	Country of origin:	Sweden
Delivered from:	Smålandsstenar		
Others:	-		

TECHNICAL DATA

Material:	Polyethylene LLD
Material additives:	-
Colour:	Transp.
Special properties:	-

<u>Parameter:</u>	<u>Value:</u>	<u>Unit:</u>	<u>Tol.±:</u>	<u>Method:</u>
Width:	500	mm	5 mm	
Thickness (nom.):	20	my	4 %	SS241013
Reel length:	1800	m	-	
Core inside Ø:	76	mm		
Core weight, approx.:	1	kg		
Gross weight approx.:	17,3	kg		
Pallet weight approx.:	519	kg		
Reels per pallet:	30			
Dartdrop:	75	g		ASTM D1709
Tensile Stress MD:	37	MPa		ISO 527-3
Elongation at break MD:	450	%		ISO 527-3
Yield point MD:	8	MPa		ISO 527-3
Rec. max. prestretch:	190	%		

ADDITIONAL INFORMATION

Man. system:	The organisation holds certificates for ISO 9001 and ISO 14001
Hygiene:	Following Reach 1907/2006/CE
Safety:	Safety datasheets and certifications available upon request
Waste handling:	All packaging components are suitable for reuse, material recycling or energy recovery

This information is only meant as guidance to simplify the choice and use of products, but cannot guarantee its suitability in specific cases.

Approved by TRIOWORLD SMÅLANDSSTENAR AB, date: 2021-06-21